

दि फ़र्टिलाइज़र्स एण्ड केमिकल्स ट्रावन्कोर लिमिटेड (भारत सरकार का उद्यम) / (A GOVERNMENT OF INDIA ENTERPRISE)	 <b>FACT</b> <b>THE FERTILISERS AND CHEMICALS</b> <b>TRAVANCORE LIMITED</b> <b>CORPORATE MATERIALS</b> PD ADMINISTRATIVE BUILDING UDYOGAMANDAL - 689 501, KOCHI, KERALA, INDIA	MAT/ESS/RFO
GST No : 32AAACT6204C1Z2 Phone : 0484-2546778 2546629 / 2545222		<b>निर्घ के लिए अनुरोध / REQUEST FOR QUOTATION</b>

**Detailed Specification**

Enquiry:MM/106/G30734

Contact Details

Name: Anitha S

Phone: 0484 2568216 , 0484 2568636

Email ID: anitha.s@factltd.com

Please submit your offer for supply of the following items as per the instructions, technical specifications and other terms and conditions specified herein/ attached.

Note:

1. The delivery period mentioned in the BoQ is our indicative requirement. You may offer your earliest delivery period.
2. Please refer our above referred enquiry number in all correspondence.

Sl.No	Material Code	Detailed Specification/s	Quantity	Unit of Measure	Plant
1	220550050	Cast Iron Butterfly Valve. Type : Wafer Type Rating : PN 10 Body : Cast Iron to IS 210 Gr FG-220 with Hypalon Rubber integrally moulded. Disc : SG Iron to IS:1865 Gr.SG 400/12 fully encapsulated with Hypalon Rubber Shaft : AISI410 with flow control lever. 100% tight. Shut-off in both flow directions against vacuum and design pressure. Manufacturing Std: BS 5155/API 609/ISO 5752.  SIZE : 50mm	6	Number	1003
2	220550080	Cast Iron Butterfly Valve. Type : Wafer Type Rating : PN 10 Body : Cast Iron to IS 210 Gr FG-220 with Hypalon Rubber integrally moulded. Disc : SG Iron to IS:1865 Gr.SG 400/12 fully encapsulated with Hypalon Rubber Shaft : AISI410 with flow control lever. 100% tight. Shut-off in both flow directions against vacuum and design pressure. Manufacturing Std: BS 5155/API 609/ISO 5752.  SIZE : 80mm	10	Number	1003
		Cast Iron Butterfly Valve. Type : Wafer Type Rating : PN 10 Body : Cast Iron to IS 210 Gr FG-220 with Hypalon Rubber integrally moulded.			

3	220550100	Disc : SG Iron to IS:1865 Gr.SG 400/12 fully encapsulated with Hypalon Rubber Shaft : AISI410 with flow control lever. 100% tight. Shut-off in both flow directions against vacuum and design pressure. Manufacturing Std: BS 5155/API 609/ISO 5752.  SIZE : 100mm	15	Number	1003
4	220550150	Cast Iron Butterfly Valve. Type : Wafer Type Rating : PN 10 Body : Cast Iron to IS 210 Gr FG-220 with Hypalon Rubber integrally moulded. Disc : SG Iron to IS:1865 Gr.SG 400/12 fully encapsulated with Hypalon Rubber Shaft : AISI410 with flow control lever. 100% tight. Shut-off in both flow directions against vacuum and design pressure. Manufacturing Std: BS 5155/API 609/ISO 5752.  SIZE : 150mm	20	Number	1003
5	220550200	Cast Iron Butterfly Valve. Type : Wafer Type Rating : PN 10 Body : Cast Iron to IS 210 Gr FG-220 with Hypalon Rubber integrally moulded. Disc : SG Iron to IS:1865 Gr.SG 400/12 fully encapsulated with Hypalon Rubber Shaft : AISI410 with flow control lever. 100% tight. Shut-off in both flow directions against vacuum and design pressure. Manufacturing Std: BS 5155/API 609/ISO 5752.  SIZE : 200mm	6	Number	1003
6	220550300	Cast Iron Butterfly Valve. Type : Wafer Type Rating : PN 10 Body : Cast Iron to IS 210 Gr FG-220 with Hypalon Rubber integrally moulded. Disc : SG Iron to IS:1865 Gr.SG 400/12 fully encapsulated with Hypalon Rubber Shaft : AISI410 with flow control lever. 100% tight. Shut-off in both flow directions against vacuum and design pressure. Manufacturing Std: BS 5155/API 609/ISO 5752.  SIZE : 300mm	2	Number	1003

**SPECIAL CONDITIONS**

1. MTC & HTC are required along with supply.
2. The material under order shall be guaranteed against poor workmanship and material for a period of 12 months from the date of commissioning or 18 months from the date of despatch, whichever is earlier.
3. Three copies of Operational / Maintenance manuals of Butterfly valves.

**# Bidder must confirm that quoted item as per FACT's required specification with duly signed copy of BoQ specification document. #**