Item Number	Item Title	Item Description	Item Quantity	Unit of Measure	Consignee ID	Delivery Period (In number of days)
1	Almirah Large with shelves steel.	Almirah Large with shelves steel. Overall size shall be 1985mm high,920mm wide and 485mm deep. The base shall be made of two numbers mild steel sheet channel bases made in U shaped with ends covered. Mild steel sheet shall be 1mm thick. The base channel shall be welded at 50mm from each end of the length of 920mm and shall be up to full width of 485mm and shall be 100mm high Top, sides bottom and back of almirah shall be of 1mm thick mild steel sheet. Four shelves equally spaced of 1mm thick mild steel sheet shall be provided to make five compartments. Front shutter shall two leaves of equal size. Front shutter leaves shall have three butt hinges of 75mm fixed to each shutter and shall be side hung. All joints and welding and fixing shall be done in accordance with the standard workmanship. One chromium plated steel handle with a locking device shall be provided as shown on drawing. The locking device shall be three way locking device and shall also be provided with decorative key plate. All steel surfaces shall be painted with two coats of silver grey hammer paint internally and extrenally with spray machine over a coat of red oxide (primer)after preparation of surfaces. A mark of MES shall also be provided on top left corner of front shutter with visible colour. Painting shall be done with spray machine. Rest all as per drg. Drg No FD 1031	6	Nos	Ageqscmbay@1	60
2	Almirah Med with shelves Steel.	Almirah Med with shelves Steel. Overall size shall be 1270mm high,765mm wide and 440mm deep. The base shall be made of two numbers mild steel sheet channel base welded to bottom of almirah and shall be 100mm high. Mild steel sheet shall be 1mm thick for channel base. The base channel shall be welded at 50mm from each end of 765mm length and shall be up to full width of 440mm of almirah. Top, sides, back, bottom and front of almirah shall be of 1mm thick mild steel sheet. Three shelves equally spaced making four compartments shall be provided and shall be of 1mm thick mild steel sheet. Front shutters shall have two leaves. All joints and welding, fixing shall be done according standard workmanship. A steel chromium plated handle 100mm long shall be provided to the shutter. The locking device shall be three way locking device and shall also be provided with decorative key plate. All steel surfaces exposed to view when placed in position shall be painted with two coats of silver hammer paint over a coat of primer with spray machine after preparation of surfaces. A mark of MES shall also be provided on left top corner of front shutter of visible colour as directed by Engr In Charge. Rest all as per drgs. FD 1032	3	Nos	Ageqscmbay@1	60
3	Table excutive with side table for officer.	Table excutive with side table for officer. Top 41mm thick made out of MDF board exterior grade and having melamine edge band with leather pad. Legs 18 mm thick MDF board exterior grade melamine edge band. Table Size 2100x1050x750mm.with storage unit. storage unit size 1200x450x670mm. As per Trade patern as per sample and directed by Engineer in Charge/GE.	3	Nos	Ageqscmbay@1	60
4	Sofa Set 5 Seater	Sofa Set 5 Seater. Sofa set 5 Seater duly covered with good quality cloth/letherrite all around and consisting of 40 density PU foam rest all as per sample and as approved by Engr in charge/ GE.	3	Nos	Ageqscmbay@1	60
5	Chair Revolving Executive	Chair Revolving Executive. Glass filled nylon backrest with limber support & mesh fabric. 4D adjustable armrest with gel PU pad. Self weight syncro till multi position lock and seatslider. 700mm aluminium diecast base & 60mm nylone castors with class 4 Gas lift. Finrest compisite leather on seat & back. Knee tilt mechnism with multiposition lock. As per Trade patern sampleand directed by Enginer in Charge.	3	Nos	Ageqscmbay@1	60